

MODEL: GF1004M | DESCRIPTION: SPEAKER

.....

FEATURES

- 102.4 mm
- square frame
- 6.0 W
- •8Ω
- ferrite magnet
- PET cone




.....

RoHS


SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
input power			6.0	10.0	W
impedance	at 0.6 kHz, 1.0 V	6.8	8	9.2	Ω
resonant frequency (Fo)	at 1.0 V	184	230	276	Hz
frequency response		Fo		14,000	Hz
sound pressure level	at 1.0 W, 50 cm, avg at 0.4, 0.5, 0.6, 0.8 kHz	91	93	95	dB
buzz, rattle, etc.	must be normal at sine wave			6.9	V
dimensions	102.4 x 102.4 x 36.5				mm
magnet	ferrite				
cone material	PET				
terminal	solder eyelets				
weight			210.0		g
operating temperature		-25		60	°C
hand soldering	for maximum 5 seconds	400	420	440	°C
RoHS	yes				

MECHANICAL DRAWING



potentiometer range	50 dB	
rectifier	RMS	
lower limit frequency	20 Hz	
wr. speed	100 mm/sec	
zero level	60 dB	



REVISION HISTORY

rev.	description	date
1.0	initial release	09/20/2006
1.01	brand update	05/18/2020
1.02	logo, datasheet style update	08/05/2022

The revision history provided is for informational purposes only and is believed to be accurate.

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.



CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.