



9615 SW Allen, Suite 103
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 372-1266
 Website: www.cui.com

Specifications

| | | | | | |
|----|--------------------|----------------------------------|-----------------|------------------------|------------|
| 1 | Part No. | GF2001 | | | |
| 2 | Nominal Size | 205 mm. | 8" | inch | |
| 3 | Impedance | 8Ω ± 15% | at | 200 Hz. | 1 V. |
| 4 | Resonance | 90 Hz.± 15 Hz. | FO Hz. | 1 V. | |
| 5 | S.P. Level | 98 dB/w ± 2 dB | 1 w. | 50 cm. | average at |
| 6 | Response | fo Hz.~ 11K Hz. | MAX 10dB | 200, 300, 400, 500 Hz. | |
| 7 | Crossover Freq. | Hz. | Hz. | dB/OCT | Net work |
| 8 | Input Power | Nominal Input | 10 w. | Handling Capacity | 20 w. |
| 9 | Operation | Must be normal at program source | | | 10 w. |
| 10 | Buzz, Rattle, etc. | Must be normal at sine wave | | | 8.9 v. |
| 11 | Flux Density | Gauss ± 10% | | | |
| 12 | Total Flux | Max well min | | | |
| 13 | Magnet | Size | 70 x 32 x 10 mm | gr | 5.3 oz |
| 14 | Total Weight | gr oz | | | |
| 15 | Load Test | After test meet item 9 and 10 | White noise | 10 W. | 48 Hours |
| 16 | Distortion | % MAX | | Hz | W. |
| 17 | Heat Test | After test meet item 9 and 10 | 70±2 ±°C | 20-50 %R.H. | 48 Hours |
| 18 | Humidity Test | After test meet item 9 and 10 | 40±2 ±°C | 90-95 %R.H. | 48 Hours |

| | | | |
|-----------|--------|----------|--------|
| PART NO. | GF2001 | UNITS: | mm |
| DRAWN BY: | | PAGE NO: | 1 of 2 |



9615 SW Allen, Suite 103
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 372-1266
 Website: www.cui.com

TITLE:

PART NO.

GF2001

UNITS:

mm

DRAWN BY:

Page No.

2 of 2