

SERIES: VUFM-S400 | **DESCRIPTION:** MEDICAL AC-DC POWER SUPPLY

FEATURES


- up to 400 W continuous power
- compact 1U size
- 5.56 W/inch³ power density
- universal input (90~264 Vac)
- single output from 3.3~48V
- short circuit, over voltage and over temperature protections
- full medical approvals
- built-in active PFC function
- built-in remote sense function
- efficiency up to 83%



| MODEL | output voltage | output current | output power | ripple and noise ⁴ | efficiency |
|---------------|----------------|----------------|------------------|-------------------------------|------------|
| | (Vdc) | max (A) | max (W) | max (mVp-p) | typ (%) |
| VUFM-S400-03R | 3.3 | 60 | 200 ¹ | 33 | 70 |
| VUFM-S400-05R | 5 | 60 | 300 ² | 50 | 75 |
| VUFM-S400-12R | 12 | 33.34 | 400 ³ | 120 | 80 |
| VUFM-S400-18R | 18 | 25 | 400 ³ | 180 | 83 |
| VUFM-S400-24R | 24 | 18.19 | 400 ³ | 240 | 83 |
| VUFM-S400-36R | 36 | 12.9 | 400 ³ | 360 | 83 |
| VUFM-S400-48R | 48 | 9.53 | 400 ³ | 480 | 83 |

- Notes:
1. total continuous output power will not exceed 200 W forced air (23 CFM), 150 W without fan
 2. total continuous output power will not exceed 300 W forced air (23 CFM), 225 W without fan
 3. total continuous output power will not exceed 400 W forced air (23 CFM), 250 W without fan
 4. 1% minimum load is required to maintain the ripple and regulation

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|-------------------------|--|-----|-----|------|-------|
| voltage | | 90 | | 264 | Vac |
| frequency | | 47 | | 63 | Hz |
| current | at 90 Vac, full load | | | 6.35 | A |
| inrush current | at 230 Vac, full load, cold start | | | 35 | A |
| input fuse | Built-in ac fuse. A blown fuse usually indicates permanent damage to the power supply serviceable by factory only. | | | | |
| power factor correction | meets EN 61000-3-2 Class D | | | | |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|---|-----|-----|-----|-------|
| total regulation | | | ±1 | | % |
| transient response | Output voltage returns to within 1% in less than 2.5 ms for a 50% load change. Peak transient does not exceed 5%. | | | | |
| start-up time | at 120 Vac | | | 1 | s |
| hold-up time | at 120 Vac, 80% load | 20 | | | ms |
| adjustability | output user adjustable | | | ±5 | % |
| switching frequency | | | 30 | | kHz |
| overshoot | Turn-on and turn-off overshoot shall not exceed 5% over nominal voltage. | | | | |
| remote sense ¹ | Designated as RS+ and RS- on CN3. Total voltage compensation for cable losses with respect to the main output. | | | | |
| remote on/off | Defined RSW on CN3, requiring a low signal to inhibit output. | | | | |
| LED display (LED 1) | Green - the power supply is operating normally. Orange - when any protection occurs or RSW is low. | | | | |
| power good | Designated as PG on CN3. This signal goes high 100~500 ms after the output reaches regulation. It goes low at least 1 ms before loss of regulation. | | | | |
| current sharing | Designated as CSH on CN3, optional single wired for forced current sharing function and parallel up to 4 units within 10% accuracy at full load. | | | | |
| current monitor | Designated as CMN on CN3 for for current sense for 0.5~3 Vdc to represent 0~100% output current. | | | | |
| AC fail (optional) | Designated as ACF on CN3 to monitor the input voltage when input goes under 80 ±5 Vac the signal will go low (0 V) and then go high (+5 V) once it reappears over 86 Vac. | | | | |

Notes: 1. Not available for current sharing models

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------------|---|-----|-----|-----|-------|
| input under voltage protection | Power supply shuts down when ac input is under 80 ±5 Vac. When ac line reappears over 86 ±5 Vac, the power supply restarts automatically. | | | | |
| over voltage protection | shutdown and latches, ac input reset required to restart | | | 130 | % |
| over current protection | auto recovery | 110 | | 140 | %Io |
| short circuit protection | auto recovery upon removal of short | | | | |
| over temperature protection | shutdown | 85 | | | °C |


SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|----------------------|--|---------|-----|-----|----------|
| isolation voltage | primary to secondary at 2 mA for 3 seconds | 4,000 | | | Vac |
| | primary to transformer core at 2 mA for 3 seconds | 1,500 | | | Vac |
| | primary to earth ground at 2 mA for 3 seconds | 1,500 | | | Vac |
| isolation resistance | allowable resistance measured when 40 A current is applied from the ground pin of the three prong plug to the farthest earthed connection point. | | | 0.1 | Ω |
| safety approvals | UL 60601-1, CSA C22.2 No. 601.1-M90, TUV EN 60601-1, CE Mark (LVD) EN 61204-3/60601-1-2/61000-3-(2,3) & IEC 61000-4 Series Regulations, CB | | | | |
| EMI/EMC | FCC Part 15, CISPR22 Class B, conducted | | | | |
| leakage current | | | | 300 | μ A |
| RoHS compliant | yes | | | | |
| MTBF | according to MIL-HBK-217F at 30°C | 100,000 | | | hours |

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|--|-----|------------|-----|------------------|
| operating temperature | derating linearly at 2.5% from 50~70°C | 0 | | 70 | °C |
| storage temperature | | -20 | | 85 | °C |
| operating humidity | non-condensing | 5 | | 90 | %RH |
| storage humidity | non-condensing | 5 | | 95 | %RH |
| vibration | 5 ~ 50 Hz, per axis | | ± 7.35 | | m/s ² |

DERATING CURVE




MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------|--|-----|-----|-----|-------|
| dimensions | 203.2 x 127 x 40.64 (8 x 5 x 1.6 inch) | | | | mm |
| weight | | | | 1.3 | kg |

MECHANICAL DRAWING

units: mm[inches]
tolerance: ±0.5[0.02]



| INPUT CONNECTOR [CN1] | | | | LOGIC CONNECTOR [CN3] | | | | FAN | |
|--|----------|--|----------|---|--------------------------|-----|------------------------|--|--|
| Howder terminal block HD-121-3P (option 1) | | Molex 09-50-3071 (7 pins, 5 used) (option 2) | | Suggested mating connector --- or equivalent Contact: SXH-002T-P0.6 | | | | --- | |
| OUTPUT CONNECTOR [CN2] | | | | PIN | FUNCTION | PIN | FUNCTION | Suggested mating connector --- or equivalent, Contact: SXH-002T-P0.6 | |
| Howder terminal block HD-121-6P (option 1) | | Molex 09-50-3161 (16 pins) (option 2) | | 1 | MAG - margin | 6 | PG - power good signal | | |
| PIN | FUNCTION | PIN | FUNCTION | 2 | CMN - current monitoring | 7 | RSW - remove on/off | | |
| 1~3 | +Vo | 1~8 | +Vo | 3 | CSH - current sharing | 8 | RS- - remote sense (-) | | |
| 4~6 | -Vo | 9~16 | -Vo | 4 | RTN - return | 9 | RS+ - remote sense (+) | | |
| | | | | 5 | ACF - AC fail | | | | |

Note: 1. Bottom mounting holes have a maximum screw depth of 3.8mm. Side mounting holes have a maximum screw depth of 6.3mm.

REVISION HISTORY

| rev. | description | date |
|------|---|------------|
| 1.0 | initial release | 07/06/2006 |
| 1.01 | updated features, added preset voltage data | 12/27/2006 |
| 1.02 | updated connector data and drawing | 12/12/2007 |
| 1.03 | new template applied | 05/11/2012 |
| 1.04 | V-Infinity branding removed | 08/28/2012 |
| 1.05 | added derating curve | 10/30/2012 |
| 1.06 | updated spec, Molex connectors changed | 01/21/2014 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC[®]

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.