


**SERIES:** EP5A 5W EU USB | **DESCRIPTION:** AC-DC POWER SUPPLY

**FEATURES**

- 5 W power
- universal input (90~264 Vac)
- single regulated 5 V output
- over voltage, over current, and short circuit protections
- TUV-GS safety approval
- level V efficiency



MODEL	output voltage (Vdc)	output current max (A)	output power max (W)	ripple and noise <sup>1</sup> max (mVp-p)	efficiency level
EP5A050100UE	5	1	5	350	V

Notes: 1. At full load, 20 MHz bandwidth oscilloscope, each output terminated with 10  $\mu$ F aluminum electrolytic and 0.1  $\mu$ F ceramic capacitors.

**PART NUMBER KEY**

**EP5A050100UE - I38 - EJ - CXX**

Base Number  
example of 5 Vdc, 1 A

USB Type A inlet

Factory Designation

Reserved for Custom Configurations

**INPUT**

parameter	conditions/description	min	typ	max	units
voltage		90		264	Vac
frequency		47		63	Hz
current	at full load			0,15	A
leakage current				0.25	mA
fuse	internal, unchangeable fuse included				

**OUTPUT**

parameter	conditions/description	min	typ	max	units
line regulation			±5		%
load regulation	from +20% to +80% load		±10		%
start-up	at 115 Vac/50 Hz, 80% max. load			2	s
hold-up	at 115 Vac/50 Hz, 80% max. load	10			ms

**PROTECTIONS**

parameter	conditions/description	min	typ	max	units
over voltage protection	output shut down				
over current protection	automatic power decrease, auto recovery			200	%
short circuit protection	output terminal protected				

**SAFETY & COMPLIANCE**

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output at 10 mA for 2 seconds	3,000			Vac
isolation resistance	input to output at 500 Vdc	10			MΩ
safety approvals	TUV-GS, CE, LPS				
EMI/EMC	CISPR22 EN55022 class B				
MTBF	as per Telcordia SR-332 at full load, 25°C	300,000			hrs
RoHS	2011/65/EU				

**ENVIRONMENTAL**


parameter	conditions/description	min	typ	max	units
operating temperature		0		40	°C
storage temperature		-25		85	°C
operating humidity		10		95	%
storage humidity		10		95	%

**MECHANICAL**

parameter	conditions/description	min	typ	max	units
dimensions	59.67 x 42.1 x 20.2				mm
input plug	EU 2-pin				

**MECHANICAL DRAWING**

units: mm  
tolerance:  $\pm 1$



PIN	Output Voltage
1	+5V
2	NC
3	NC
4	GND

+5		1
GND		4

## REVISION HISTORY

rev.	description	date
1.0	initial release	11/06/2013

The revision history provided is for informational purposes only and is believed to be accurate.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



**CUI INC**<sup>®</sup>

**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com