



SERIES: EMC-05B | **DESCRIPTION:** AC POWER LINE FILTER

FEATURES

- reduces emissions to help comply with CISPR22 / EN 55022 Class B
- protects against surge events and Electrical Fast Transients
- wide input voltage range (85 ~ 305 Vac)
- 0.5 A rated current
- -40 to +85°C temperature range
- options for board and chassis mounting


SPECIFICATIONS

| parameter | conditions/description | min | typ | max | units |
|----------------------------------|---|-----|-----|-----|-------|
| input voltage | | 85 | | 305 | Vac |
| input current | | | | 0.5 | A |
| RoHS | yes | | | | |
| operating temperature | | -40 | | 85 | °C |
| storage temperature | | -40 | | 105 | °C |
| storage humidity | non-condensing | | | | |
| case temperature rise | at 220 Vac, 0.05 A | | | 5 | °C |
| | at 220 Vac, 0.25 A | | | 20 | °C |
| | at 220 Vac, 0.5 A | | | 30 | °C |
| leakage current (line to ground) | 2000 Vac, tested for 1 minute | | 2 | | mA |
| noise attenuation | 150 kHz ~ 1 GHz: EMC-05B | | 30 | | dB |
| EFT | IEC/EN61000-4-4 | | ±4 | | kV |
| surge | IEC/EN61000-4-5, +/-4 kV (2 ohms) / +/-6 kV (12 ohms) | | | | |

PART NUMBER KEY


MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|---------------|--|-----|--------|-----|-------|
| dimensions | board mount - 62.00 x 45.00 x 22.50 [2.44 x 1.77 x 0.89 inch] chassis mount - 96.10 x 54.00 x 31.00 [3.78 x 2.13 x 1.22 inch] | | | | mm |
| case material | black flame-retardant heat-proof epoxy resin (UL94-V0) | | | | |
| weight | board mount, chassis mount | | 85/135 | | g |



MECHANICAL DRAWING (BOARD MOUNT-B)

units: mm [inch]

tolerance: ±0.50 [±0.020]

pin diameter tolerance: ±0.50 [±0.020]

| PIN-OUT | |
|---------|----------|
| PIN | Function |
| 1 | GND |
| 2 | IN(N) |
| 3 | IN(L) |
| 4 | OUT(N) |
| 5, 6, 7 | NC |
| 8 | OUT(L) |




Note: Grid 2.54*2.54mm
Recommended PCB Layout
Top View

| Supporting Product Table | | | | | | |
|--------------------------|--------------------------------|-------------------------|----------------------------|-----------------------|------------------------------|-------------------------|
| Model | EMI (without external circuit) | EMI (with EMC filter) | EFT (w/o external circuit) | EFT (with EMC filter) | Surge (w/o external circuit) | Surge (with EMC filter) |
| VSK-S1 | CISPR22/EN55022 CLASS B | - | - | IEC/EN61000-4-4 ±2KV | - | IEC61000-4-5 ± 4KV/±6KV |
| VSK-S2 | CISPR22/EN55022 CLASS B | - | - | IEC/EN61000-4-4 ±2KV | - | IEC61000-4-5 ± 4KV/±6KV |
| VSK-S3 | CISPR22/EN55022 CLASS A | CISPR22/EN55022 CLASS B | - | IEC/EN61000-4-4 ±2KV | - | IEC61000-4-5 ± 4KV/±6KV |
| VSK-S5 | CISPR22/EN55022 CLASS A | CISPR22/EN55022 CLASS B | IEC/EN61000-4-4 ±2KV | IEC/EN61000-4-4 ±4KV | IEC/EN61000-4-5 ±1K /±2KV | IEC61000-4-5 ± 4KV/±6KV |
| VSK-S10 | CISPR22/EN55022 CLASS A | CISPR22/EN55022 CLASS B | IEC/EN61000-4-4 ±2KV | IEC/EN61000-4-4 ±4KV | IEC/EN61000-4-5 ±1K | IEC61000-4-5 ± 4KV/±6KV |

MECHANICAL DRAWING (CHASSIS MOUNT)

units: mm [inch]
 tolerance: ± 0.50 [± 0.020]
 wire range: 24~12 AWG
 dimensions: 96.1 x 54 x 31 mm


| PIN | Function |
|-----|----------|
| 1 | GND |
| 2 | IN(N) |
| 3 | IN(L) |
| 4 | OUT(N) |
| 5 | NC |
| 6 | NC |
| 7 | NC |
| 8 | OUT(L) |




EMC SPECIFICATIONS

The EMC-05B model increases the surge protection to IEC/EN61000-4-5 ±4KV (2Ω internal resistance)/±6KV (12Ω internal resistance) levels. This model assists in meeting EMI requirements according to CISPR22 /EN 55022 Class B.

Figure 1
Internal Circuit




EMC-05B



Input voltage waveform (Differential mode 4.06KV)



Output voltage waveform (0.75KV)




Input voltage waveform (Common mode 6.06KV)



Output voltage waveform(0.5KV)

APPLICATION CIRCUIT

Figure 2
Application Circuit



REVISION HISTORY

| rev. | description | date |
|------|------------------------------|------------|
| 1.0 | initial release | 12/10/2019 |
| 1.01 | din-rail mount model removed | 04/09/2021 |
| 1.02 | circuit figures updated | 01/12/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.