CUI INC
a bel group



# **SERIES:** VGS-150C | **DESCRIPTION:** INTERNAL AC-DC POWER SUPPLY

## FEATURES

- universal input range (85 ~ 264 VAC)
- UL/EN/IEC 62368 certified
- designed to meet IEC/EN 61558, IEC/EN 60335, and GB4943 system requirements
- short-circuit, over-current, over-voltage, over-temperature protections
- input over voltage category III for fixed installations (under 2,000 m altitude)
- CISPR/EN55032 Class B radiated/conducted emissions
- output adjustable via trimpot +/- 10%

| MODEL | output voltage (Vdc) | output current max (A) | output power max (W) | ripple and noise[1] typ (mVp-p) | efficiency[2] typ (%) |
|---|---|---|---|---|---|
| VGS-150C-12 | 12 | 12.5 | 150.0 | 150 | 86 |
| VGS-150C-15 | 15 | 10.0 | 150.0 | 150 | 87 |
| VGS-150C-24 | 24 | 6.5 | 156.0 | 200 | 88 |
| VGS-150C-36 | 36 | 4.3 | 154.8 | 200 | 88 |
| VGS-150C-48 | 48 | 3.3 | 158.4 | 200 | 89 |

Notes: 1. Ripple & noise are measured at 20 MHz BW with 47 μF aluminum electrolytic capacitor and 0.1 μF ceramic capacitor on the output.
2. Measured at 230 Vac

## PART NUMBER KEY

**VGS-150C - XX - X**

- VGS-150C: Base Number
- XX: Output Voltage
- X: A - with terminal cover; B - with conformal coating

## INPUT

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| voltage | ac input<br>dc input | 85<br>120 | | 264<br>373 | Vac<br>Vdc |
| frequency | | 47 | | 63 | Hz |
| current | at 115 Vac<br>at 230 Vac | | | 4<br>2 | A<br>A |
| inrush current | at 115 Vac, cold start<br>at 230 Vac, cold start | | 30<br>60 | | A<br>A |
| leakage current | at 240 Vac | | | 0.75 | mA |
| no load power consumption | | | | 0.5 | W |

## OUTPUT

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| capacitive load | 12 Vdc output<br>15 Vdc output<br>24 Vdc output<br>36 Vdc output<br>48 Vdc output | | | 10,000<br>6,000<br>2,400<br>1,200<br>600 | µF<br>µF<br>µF<br>µF<br>µF |
| initial set point accuracy | at full load | | ±1 | | % |
| line regulation | | | ±0.5 | | % |
| load regulation | 0%~100% load | | ±0.5 | | % |
| adjustability | built in trim pot | ±10 | | | % |
| hold-up time | at 115 Vac<br>at 230 Vac | 8<br>16 | | | ms<br>ms |
| switching frequency | | | 65 | | kHz |
| temperature coefficient | | | ±0.05 | | %/°C |

## PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| over voltage protection | 12 Vdc output, output shut-down, restart required to recover<br>15 Vdc output, output shut-down, restart required to recover<br>24 Vdc output, output shut-down, restart required to recover<br>36 Vdc output, output shut-down, restart required to recover<br>48 Vdc output, output shut-down, restart required to recover | | | 16.2<br>21.75<br>33.6<br>48.6<br>60.0 | Vdc<br>Vdc<br>Vdc<br>Vdc<br>Vdc |
| over current protection | auto-recovery | 110 | | 150 | % |
| short circuit protection | hiccup, continuous, auto-recovery | | | | |
| over temperature protection | auto-recovery | | | | |

## SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| isolation voltage | input to ground<br>input to output<br>output to ground | 2,000<br>4,000<br>1,250 | | | Vac<br>Vac<br>Vac |
| safety approvals | certified to: 62368: IEC/EN/UL<br>designed to meet: 60335: IEC/EN<br>designed to meet: 61558: IEC/EN<br>designed to meet: 4943: GB | | | | |
| safety class | Class I | | | | |
| EMI/EMC | CISPR32/EN55032 Class B, IEC/EN61000-3-2 Class A (≤80% load) | | | | |
| ESD | IEC/EN 61000-4-2 Contact ±6KV /Air ±8KV, perf. Criteria A | | | | |
| radiated immunity | IEC/EN 61000-4-3 10V/m, perf. Criteria A | | | | |
| EFT/burst | IEC/EN 61000-4-4 ±4KV, perf. Criteria A | | | | |
| surge | IEC/EN 61000-4-5 line to line ±2KV/line to ground ±4KV, perf. Criteria A | | | | |
| conducted immunity | IEC/EN61000-4-6 10 Vr.m.s, perf. Criteria A | | | | |

## SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| voltage dips and interruptions | IEC/EN61000-4-11 0%, 70%, perf. Criteria B | | | | |
| MTBF | as per MIL-HDBK-217F at 25°C | 300,000 | | | hours |
| RoHS | yes | | | | |

## ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| operating temperature | | -30 | | 70 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | non-condensing | 20 | | 90 | % |
| storage humidity | non-condensing | 10 | | 95 | % |

## MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| dimensions | 159.00 x 97.00 x 30.00 | | | | mm |
| weight | | | 410 | | g |
| cooling | natural convection | | | | |
| case material | metal (AL1100, SGCC) | | | | |

## MECHANICAL DRAWING

units: mm [inch]
tolerance: ±1.0 [±0.039]
wire range: 22-12 AWG
connector tightening torque: M3.5, 0.8 N·m

| PIN CONNECTIONS | |
|---|---|
| PIN | Function |
| 1 | AC(L) |
| 2 | AC(N) |
| 3 | ⏚ |
| 4 | -Vo |
| 5 | -Vo |
| 6 | +Vo |
| 7 | +Vo |




| Position | Screw spec. | L (max) | Torque (max) |
|---|---|---|---|
| ② - ④ | M3 | 5 mm | 0.4 N·m |
| ⑦ - ⑧ | M3 | 3 mm | 0.4 N·m |

Note: At least one hole position, ①~⑨, must be securely connected to Protective Earth (PE) ⏚

## DERATING CURVE







## EFFICIENCY CURVES






## REVISION HISTORY

| rev. | description | date |
|---|---|---|
| 1.0 | initial release | 09/28/2020 |
| 1.01 | over temperature protection added to protections section | 04/06/2021 |
| 1.02 | derating and efficiency curves updated | 02/02/2022 |
| 1.03 | OVP and derating curve updated | 05/12/2022 |
| 1.04 | UKCA mark added | 06/06/2022 |
| 1.05 | features updated | 01/09/2024 |

The revision history provided is for informational purposes only and is believed to be accurate.

CUI INC
a bel group

**Headquarters**
20050 SW 112th Ave.
Tualatin, OR 97062
**800.275.4899**

Fax 503.612.2383
**cui**.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.