



### **Declaration of Conformity**

Manufacturer: CUI Inc 20050 SW 112th Ave Tualatin, OR 97062

For the following equipment:

DC-DC Converter

#### **CUI Series: PDQE30-D**

Models: 48V nominal input, see next page

This declaration of conformity is issued under the sole responsibility of the manufacturer. The object of the declaration described above is in conformity with the relevant Union harmonization legislations and their amendments:

Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU and (EU) 2015/863

References to the relevant harmonized standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared:

**Health & Safety** 

EN 62368-1:2014+A11:2017

EMC

EN 55032:2015+A11:2020; EN 55035:2017+A11:2020

RoHS

EN IEC 63000:2018

Note: These component level power supplies are intended exclusively for inclusion within other equipment. Protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.

(222)	1
1	Men
11	Num

Shenzhen, China

12/25/2023

(date)

(manufacturer)

Link Lu Product Compliance Specialist

Colomon vagara

(manufacturer)

Tualatin, Oregon, USA (place)

(place)

12/25/2023

(date)

Editha Vergara Global Director, Safety, Environmental

Bel Power Solutions & Protection (a bel group)

2nd Floor, Citygate House, Ballycummin Avenue, Raheen Business Park, Limerick, V94 H9YE, Ireland | t +353 61 498 955

www.cui.com

Page 1 of 3



# **MODEL LIST**

\_

PDQ	PDQE30-Q48-SXX-D (where XX = 5, 12, 15, 24 denote output voltage)						
Model		Input voltage (typ.)	Input voltage (range)	Output voltage (Vdc)			
	PDQE30-Q48-S5-D	48	18-75	5			
	PDQE30-Q48-S12-D	48	18-75	12			
	PDQE30-Q48-S15-D	48	18-75	15			
	PDQE30-Q48-S24-D	48	18-75	24			

# Model Naming Configuration

PQDE30	-	Q	XX	-	S	XX	-	D
Ι	-		II	-		III	-	IV

Ι	-	Base Number:	PDQE30
II	-	Nom. Input Voltage:	48 = 48

Output Voltage: 5 = 5 V; 12 = 12 V; 15 = 15 V; 24 = 24 V

48 V

D = DIP

III IV Packaging Style: \_

> Bel Power Solutions & Protection (a bel group) 2nd Floor, Citygate House, Ballycummin Avenue, Raheen Business Park, Limerick, V94 H9YE, Ireland | t +353 61 498 955 www.cui.com

Page 2 of 3



# **REVISION HISTORY**

rev.	description	date
1.0	initial release	12/25/23

The revision history provided is for informational purposes only and is believed to be accurate.

Page **3** of **3**