



## Declaration of Conformity

Manufacturer:  
**CUI Inc**  
20050 SW 112th Ave  
Tualatin, OR 97062

For the following equipment:

DC-DC Converter  
**CUI Series: VHB350**  
Models: 48V nominal input, see next page

This declaration of conformity is issued under the sole responsibility of the manufacturer.  
The object of the declaration described above is in conformity with the relevant Union harmonization legislations and their amendments:

**Low Voltage Directive 2014/35/EU**  
**EMC Directive 2014/30/EU**  
**RoHS Directive 2011/65/EU and (EU) 2015/863**

References to the relevant harmonized standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared:

<b>Health &amp; Safety</b>	EN 62368-1:2014+A11:2017
<b>EMC</b>	EN 55032:2015+A11:2020; EN 55035:2017+A11:2020
<b>RoHS</b>	EN IEC 63000:2018

Note: These component level power supplies are intended exclusively for inclusion within other equipment. Protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.

(manufacturer)

Link Lu  
Product Compliance Specialist

**Shenzhen, China**

(place)

**05/07/2024**

(date)

(manufacturer)

Editha Vergara  
Global Director, Safety, Environmental

**Tualatin, Oregon, USA**

(place)

**05/07/2024**

(date)

## MODEL LIST

VHB350-D48-SXX (where XX = 3R3, 5, 12, 24, 48 denote output voltage)

VHB350-D48-SXXN (where XX = 3R3, 5, 12, 24, 48 denote output voltage)

Model	Input voltage (typ.)	Input voltage (range)	Output voltage (Vdc)
VHB350-D48-S3R3	48	36-75	3.3
VHB350-D48-S5	48	36-75	5
VHB350-D48-S12	48	36-75	12
VHB350-D48-S24	48	36-75	24
VHB350-D48-S48	48	36-75	48
VHB350-D48-S3R3N	48	36-75	3.3
VHB350-D48-S5N	48	36-75	5
VHB350-D48-S12N	48	36-75	12
VHB350-D48-S24N	48	36-75	24
VHB350-D48-S48N	48	36-75	48

## Model Naming Configuration

VHB350	-	D	XX	-	S	XX	X
I	-		II	-		III	IV

- I - Base Number: VHB350
- II - Nom. Input Voltage: 24 = 24 V; 48 = 48 V
- III - Output Voltage: 3R3 = 3.3 V; 5 = 5 V; 12 = 12 V; 24 = 24 V; 48 = 48 V
- IV - Remote On/Off Control: Blank = Positive Logic  
N = Negative Logic

## REVISION HISTORY

---

<b>rev.</b>	<b>description</b>	<b>date</b>
1.0	initial release	05/07/24

The revision history provided is for informational purposes only and is believed to be accurate.