

SERIES: PDRB-100 | **DESCRIPTION:** AC-DC DIN RAIL POWER SUPPLY
FEATURES


- universal input range (85 ~ 264 Vac)
- IEC/EN/UL 62368 certified
- designed to meet 61558 system requirements
- over Voltage Category (OVC) III design
- over voltage, over current, and short circuit protections
- 4kVac isolation input to output
- withstand up to 300 Vac input surge events
- Class B emissions



MODEL	output ¹ voltage		output current	output power	ripple and noise ²	efficiency ³
	(Vdc)	range (Vdc)	max (A)	max (W)	max (mVp-p)	typ (%)
PDRB-100-12	12	12.0 ~ 13.8	7.5	90.0	120	88
PDRB-100-15	15	13.5 ~ 18.0	6.5	97.5	120	89
PDRB-100-24	24	21.6 ~ 29.0	4.2	100.8	150	90
PDRB-100-48	48	43.2 ~ 55.2	2.1	100.8	240	90

Notes:

1. Output adjustable via built-in trimpot. The actual adjustment range may extend beyond the values listed and care should be taken to ensure the output voltage and output power do not exceed stated limits.
2. At full load, nominal input, 20 MHz bandwidth oscilloscope.
3. At 230 Vac input.

PART NUMBER KEY

INPUT

parameter	conditions/description	min	typ	max	units
input voltage	ac input	85		264	Vac
	dc input	120		370	Vdc
frequency		47		63	Hz
current	at 115 Vac			3.0	A
	at 230 Vac			1.6	A
inrush current	at 115 Vac		35		A
	at 230 Vac		70		A
leakage current	at 240 Vac			0.5	mA

OUTPUT

parameter	conditions/description	min	typ	max	units
capacitive load	12 Vdc output models			10,000	μF
	15 Vdc output models			6,400	μF
	24 Vdc output models			2,500	μF
	48 Vdc output models			1,100	μF
initial set point accuracy	0% ~ 100% load		±2		%
line regulation	at rated load		±0.5		%
load regulation	at 230 Vac		±1.5		%
start-up time				3	s
hold-up time	at 230 Vac		30		ms
switching frequency			65		kHz
temperature coefficient			±0.03		%/°C
no load power consumption	at 230 Vac			0.3	W
	12 Vdc, 15 Vdc output models			0.35	W
	24 Vdc output models			0.4	W
	48 Vdc output models				W

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	12 Vdc output models			20	Vdc
	15 Vdc output models			25	Vdc
	24 Vdc output models			35	Vdc
	48 Vdc output models			60	Vdc
over current protection	auto recovery	110		200	%
short circuit protection	continuous, auto recovery, hiccup				

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output 5 mA for 1 minute	4,000			Vac
safety approvals	certified to 62368:IEC, EN, UL/cUL				
safety class	Class II				
conducted emissions	CISPR32/EN55032 CLASS B				
radiated emissions	CISPR32/EN55032 CLASS B				
ESD	IEC/EN61000-4-2 Contact ±6KV/Air ±8KV perf. Criteria A				
radiated immunity	IEC/EN61000-4-3 10V/m perf. Criteria A				
EFT/burst	IEC/EN61000-4-4 ±4KV perf. Criteria A				
surge	IEC/EN61000-4-5 line to line ±2KV perf. Criteria A				
conducted immunity	IEC/EN61000-4-6 10Vr.m.s perf. Criteria A				
voltage dips and interruption	IEC/EN61000-4-11 0%, 70% perf. Criteria A				
MTBF	as per MIL-HDBK-217F at 25°C	300,000			hours
RoHS	yes				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-40		70	°C
storage temperature		-40		85	°C
storage humidity	non-condensing	0		95	%
altitude				2,000	m


MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	70.00 x 92.66 x 58.00				mm
material	plastic, heat-resistant (UL94V-0)				
weight			235		g
cooling	natural convection				


MECHANICAL DRAWING

units: mm [inch]
 ADJ: built-in trimpot
 wire range: 24-12 AWG
 tightening torque: Max 0.4 N·m
 mounting rail: TS35
 general tolerances: ±1.0 [±0.039]


TERMINAL CONNECTIONS	
TERMINAL	Function
1	AC (L)
2	AC (N)
3	+Vo
4	+Vo
5	-Vo
6	-Vo



DERATING CURVE



EFFICIENCY CURVES



REVISION HISTORY

rev.	description	date
1.0	initial release	11/25/2020

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.