


**SERIES: VBM-360 | DESCRIPTION: AC-DC POWER SUPPLY**
**FEATURES**

- up to 360 W continuous power
- baseplate cooling
- industry standard 3" x 5" footprint
- universal input (90~264 Vac)
- single output from 12 to 48V
- over voltage, short circuit, and over temperature protections
- built-in active PFC function
- built-in remote sense function
- remote on/off control function
- efficiency up to 93.5%



MODEL	output voltage	output current	output power	ripple and noise <sup>1</sup>	efficiency
	(Vdc)	max (A)	max (W)	max (mVp-p)	typ (%)
VBM-360-12	12	29.6	355	120	92.5
VBM-360-24	24	14.8	355	150	93.5
VBM-360-48	48	7.4	355	150	93.5

Notes: 1. at 20 MHz bandwidth oscilloscope, each output terminated with a 47  $\mu$ F electrolytic and 0.1  $\mu$ F ceramic capacitors.

**PART NUMBER KEY**


## INPUT

parameter	conditions/description	min	typ	max	units
voltage		90		264	Vac
frequency		47		63	Hz
inrush current	at 240 Vac			50	A
leakage current	at 264 Vac			3.5	mA

## OUTPUT

parameter	conditions/description	min	typ	max	units
line regulation	high line to low line, full load		±0.5		%
load regulation	60% ±40% rated load		±1		%
voltage accuracy	set at 60% rated load and 25°C		±1		%
hold-up time			12		ms
adjustability	built in trim pot			±5	%
switching frequency		55		60	kHz
temperature coefficient			±0.05		%/°C
standby output	5 Vdc / 0.5A				
fan drive output	12 Vdc / 0.3A for external fan				

## PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	recycle ac input to restart				
short circuit protection	hiccup mode, recovers automatically				
over temperature protection	auto recovery				
over current protection	continuous	120		150	%

## SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output	3,000			Vac
safety approvals	IEC 60950-1, EN 60950-1, UL 60950-1				
EMI/EMC	EN 55022 Class B, FCC Part 15 Class B, EN 61000-6-(1,3), EN 61000-3-(2,3), EN 55024, EN 61204-3				
RoHS compliant	yes				


## ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	refer to derating curves for more details	-20		85	°C
storage temperature		-40		85	°C
operating humidity	non-condensing			93	%

## DERATING CURVES


### VBM-360 (open frame)

Natural Convection  
(Ambient Temp vs. Load)




### VBM-360-CNF (enclosed)


Natural Convection  
(Ambient Temp vs. Load)




Natural Convection  
(Input Voltage vs. Load)  
40 °C




Natural Convection  
(Input Voltage vs. Load)  
40 °C




10 CFM Airflow  
(Ambient Temp vs. Load)  
90~264 Vac



10 CFM Airflow  
(Ambient Temp vs. Load)  
90~264 Vac



Baseplate Cooling  
(Ambient Temp vs. PD)  
90~264 Vac



## MECHANICAL


parameter	conditions/description	min	typ	max	units
dimensions	open frame	5.000 x 3.000 x 1.598 (127.00 x 76.20 x 40.60 mm)			inch
	enclosed	5.391 x 3.425 x 1.697 (136.94 x 87.00 x 43.10 mm)			inch
weight	open frame		470 1.04		g lbs
	enclosed		550 1.21		g lbs

## MECHANICAL DRAWING

units: inch[mm]


TOLERANCE: inch: ±0.02  
mm: ±0.5

### Open Frame




CN1	
1	AC Line
2	No pin
3	AC Neutral

### Enclosed (CNF)



CN2			
1	+S	8	-S
2	GND	7 <sup>1</sup>	enable
3	GND	6	+5 VBS
4	FAN output-	5	FAN output+



Note: 1. pull down enable to activate the power supply (pin 7 tied to Pin 2).

## REVISION HISTORY

rev.	description	date
1.0	initial release	01/09/2013
1.01	added baseplate cooling to features, updated derating curves	02/04/2013

The revision history provided is for informational purposes only and is believed to be accurate.



**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.